

Bobcat® Planer Attachment

Specifications

Planer	14-in. Standard-Flow	15-in. Curb Planer	16-in. Surface Planer	18-in. High-Flow	24-in. High-Flow	40-in. High-Flow
Weight	1460 lb. (662 kg) (w/drum)	1430 lb. (649 kg) (w/o drum)	1595 lb. (723 kg) (w/drum)	1260 lb. (572 kg) (w/o drum)	1400 lb. (635 kg) (w/o drum)	2300 lb. (1043 kg) (w/drum)
Overall Width	66 in. (1676 mm)	70.4 in. or 86.9 in.	66 in. (1676 mm)	66 in. (1676 mm)	66 in. (1676 mm)	68 in. (1727 mm)
Overall Length	49 in. (1245 mm)	49 in. (1245 mm)	49 in. (1245 mm)	49 in. (1245 mm)	49 in. (1245 mm)	44 in. (1118 mm)
Overall Height	28 in. (711 mm)	28 in. (711 mm)	28 in. (711 mm)	28 in. (711 mm)	28 in. (711 mm)	32 in. (813 mm)
Standard Drum Cutting Width	14 in. (356 mm)	Standard Drum 15 in. (381 mm)	16 in. (406 mm)	18 in. (457 mm)	24 in. (610 mm)	40 in. (1016 mm)
Drum Diameter	17.75 in. (451 mm)	17.75 in. (451 mm)	17.75 in. (451 mm)	17.75 in. (451 mm)	17.75 in. (451 mm)	14.5 in. (368 mm)
Cutting Depth	0-6 in. (152 mm)	0-5 in. (127 mm) flat, Up to 8-in. (203 mm) curb	0-6 in. (152 mm)	0-6 in. (152 mm)	0-6 in. (152 mm)	0-5 in. (127 mm)
Maximum Cutting Angle	±15 deg.	±15 deg. (Hydraulic)	±15 deg.	±15 deg.	±15 deg.	±8 deg. (Hydraulic)
Side-Shift (Hydraulic)	26 in. (660 mm)	26 in. (660 mm)	26 in. (660 mm)	26 in. (660 mm)	26 in. (660 mm)	25.6 in. (650 mm)
Planing Distance Next to Curb (if loader width is less than:)	Flush (72 in.)	Flush (101 in.)	Flush (72 in.)	Flush (72 in.)	Flush (79 in.)	(3 in.)

Planer Drums Available

Cutting Widths	Type of Drum	Number of Bits	Weight with Bits
2 1/2 in. (64 mm)	Slot Cut	21	90 lb. (41 kg)
4 in. (102 mm)	Slot Cut	24	110 lb. (50 kg)
6 in. (152 mm)	All Purpose	32	155 lb. (70 kg)
8 in. (203 mm)	All Purpose	34	180 lb. (82 kg)
12 in. (305 mm)	All Purpose	40	225 lb. (102 kg)
14 in. (356 mm)	All Purpose	46	240 lb. (109 kg)
15 in. (381 mm)	Smooth Cut, Curb	72	275 lb. (125 kg)
16 in. (406 mm)	Fast Cut	47	270 lb. (122 kg)
16 in. (406 mm)	Smooth Cut	84	320 lb. (145 kg)
16 in. (406 mm)	Surface	184	300 lb. 136 kg)
18 in. (457 mm)	Fast Cut	47	285 lb. (129 kg)
18 in. (457 mm)	Smooth Cut	84	340 lb. (154 kg)
24 in. (610 mm)	Fast Cut	57	355 lb. (161 kg)
24 in. (610 mm)	Smooth Cut	124	460 lb. (209 kg)

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for loader equipped with standard tires. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

The Bobcat Attachments Advantage: Bobcat attachments are engineered and manufactured to fit Bobcat loaders for optimum job performance, dependability and durability.

Bobcat 14", 16", 18" and 24" Planers feature:

- Top access panel for easier bit service and maintenance.
- Side cutting bits to decrease drum binding in the cut and to produce a vertical edge for improving the joint bond between a new layer of asphalt and the existing layer.
- Hydraulic side-shift for planing close to walls and curbs, and to easily reposition the drum for another pass.
- Oscillating planer housing for planing sloped surfaces or to match two uneven surfaces.
- Rear frame wheels to provide support and reduce tire bounce while planing.
- Direct-drive high torque motors for low maintenance and high efficiency.
- Bob-Tach™ mounting system with quick-connect controls for fast, easy attachment changes.
- Unmatched Bobcat parts and service support.
- Operator training kits available for both loader and planer attachment.

Bobcat Planer Attachment fits these carrier models:**

Skid-Steer Loaders:

S130
S150
S160
S160H
S175
S175H
S185
S185H
S205
S205H
S220
S220H
S250
S250H
S300
S300H

Compact Track Loaders:

T140
T180
T180H
T190
T190H
T250
T250H
T300
T300H

All-Wheel Steer Loaders:

A300
A300H

McDOWELL BROTHERS INDUSTRIES INC
2018 KINGSWAY BLVD.
SUDBURY, ONTARIO P3B 4J8
CANADA
(705) 566-8190



B-1582 (1/07)

Bobcat Company
P.O. Box 6000 • West Fargo, ND 58078
www.bobcat.com

Printed in U.S.A.



Kn-10M-107-#5965-F

**See planer models inside for specific loader applications